



## RESIN INFORMATION SHEET

<b>Product Name</b>	<b>TOYOPEARL® HW-65</b> (Size exclusion chromatography resin)	
<b>Part Numbers</b>	0019815	TOYOPEARL HW-65S, 150 mL
	0007467	TOYOPEARL HW-65S, 250 mL
	0007464	TOYOPEARL HW-65S, 500 mL
	0014688	TOYOPEARL HW-65S, 1 L
	0008068	TOYOPEARL HW-65S, 5 L
	0018377	TOYOPEARL HW-65S, 50 L
	0019814	TOYOPEARL HW-65F, 150 mL
	0007465	TOYOPEARL HW-65F, 500 mL
	0014689	TOYOPEARL HW-65F, 1 L
	0008069	TOYOPEARL HW-65F, 5 L
	0021852	TOYOPEARL HW-65F, 50 L
	0021481	TOYOPEARL HW-65C, 150 mL
	0007466	TOYOPEARL HW-65C, 500 mL
	0014690	TOYOPEARL HW-65C, 1 L
	0008070	TOYOPEARL HW-65C, 5 L
	0021482	TOYOPEARL HW-65C, 50 L
<b>Product Description</b>	<p>TOYOPEARL chromatographic resins are based on a rigid methacrylic polymer, resulting in high mechanical and chemical stability. Resins are available as non-functionalized “HW” series resins for size exclusion separations, and derivatized with surface chemistries for alternative modes of chromatography such as ion exchange, hydrophobic interaction or affinity separations.</p> <p>TOYOPEARL HW-65 chromatographic resin is designed for aqueous size exclusion chromatography (also known as gel filtration chromatography). This chromatographic mode separates molecules on the basis of molecular hydrodynamic radius. These resins possess controlled pore distribution such that molecules with dynamic radii smaller than the pores diffuse throughout the accessible volume of the bead and are thus separated from larger molecules that are excluded from smaller pores. The separation is normally accomplished in aqueous solution of moderate ionic strength (100 - 300mM) to reduce interaction with residual negative charges on the matrix.</p>	
<b>Operating Conditions</b>	Packing pressure	Typically 0.3 MPa
	Shipping solvent	20 % (v/v) ethanol
	Shipping formulation	72 % (v/v) slurry in shipping solvent (*)
	Pressure limiting factor	Depend on column hardware (typically 0.7 MPa)
	Operating linear flowrate	Typically 10 - 600 cm/hour
	Long-term storage conditions	20 % (v/v) ethanol
	Cleaning-in-place/Sanitization	0.1 - 0.5 mol/L NaOH or 0.1 mol/L HCl
<b>Specifications</b>	Particle size distribution (min. 80 % within range)	20 - 40 µm for S-grade 30 - 60 µm for F-grade 50 - 100 µm for C-grade
	Exclusion limit (MW of PEO)	(0.70 - 1.30) x 10 <sup>6</sup>
	Bacterial count	Max. 100 CFU/mL
	Endotoxin concentration	Max. 10.0 EU/mL
	Eluable matter	Max. 0.2 % (for dry gel)
	Foreign substance (colored particle)	Unobserved
<b>Additional Information</b>	Appearance	White resin slurry which settles upon standing
	Mean pore diameter (base resin)	100 nm (*)

(\*) The value is for reference only, not guaranteed.

Lot-specific data are included in the Certificate of Analysis (COA) shipped with the product. For detailed test procedures please refer to the appropriate Regulatory Support File.